



FU WEI

Bushing Cut-Off 2Die 3Blow with Fingerless Transfer

MODEL DESCRIPTION	UL-2305	UL-2310	UL-2315
(MM)WIRE DIAMETER	Φ1.2- Φ2.5	Φ1.4- Φ3.5	Φ1.6- Φ4.5
(MM)CUT-OFF LENGTH	2~14	3~25	3~30
(MM)KO LENGTH /MAX	14	25	30
BLANK PER MIN MAX	50-120 PCS	50-110 PCS	50-100 PCS
(MM)MAIN SLIDER STROKE	45	60	92
(MM)MAIN UP/DOWN STROKE	26	26	32
(MM)P.K.O. STROKE	non	3rd 10	3rd 12
MAIN MOTOR	1HP-6P	3HP-6P	5HP-4P
(MM)1ST DIE DIA.	Φ14x25L	Φ20x35L	Φ22X62 L
(MM)2ND DIE DIA.	Φ20x35. 3L	Φ30x50. 3L	Φ34.5X8 0.5L
(MM)1ST PUNCH DIA.	Φ14x50L	Φ16x40L	Φ18X70 L
(MM)2ND PUNCH DIA.	Φ18 x50L	Φ26x63L	Φ28X75 L
(MM)THIRD PUNCH DIA.	Φ18 x50L	Φ18 x63L	Φ25X75 L
(MM)CUT-OFF DIA.	φ12	φ15	φ19
(MM)CUTTER	6X20X55	8X24X70	9x32x75
N.W.KG	750	1000	1450
G.W.KG	850	1100	1550
(CM)OVERALL DIMENSION(LxWxH)	210X120 X147	225X112 X148	225x112 x148

**Please call if you need further assistance.
Thanks for visiting truformequipment.com**