



SPECIFICATIONS	MODEL	TR-10T	TR-5T
Range of thread	Max. diameter	□50 mm	□50 mm
	Min. diameter	□5 mm	□2 mm
	Pitch	0.6-2.5 mm	0.25-2 mm
	Range of length (in-feed)	5-70 mm	5-50 mm □2-12
	Range of length (thru-feed)	under 35: Free From 35- 50:Within 300L	under 12: Free From 12-50:Within 300L
Speed range	0-100 RPM(Standard) TR-10T, TR-5T 112-252 RPM(Optional) TR-10T		
Rolling Dies	Max. diameter	□130 mm	□100 mm
	Bore diameter	□54 mm	□35/40 mm
	Width range	70 mm	50 mm
	Key way	10 mm	8 mm
Dies spindle	Max. diameter	160mm	151 mm
	Min. diameter	100 mm	100 mm
Max. rolling pressure		10 Tons	5 Tons
Main power		7.5HP (5.6kw)	2HP (1.5kw)
Hydraulic power		3HP (2.2kw)	2HP (1.5kw)
Coolant power		1/8HP (0.09kw)	1/8HP (0.09kw)
Height from floor to spindle center		810 mm	760 mm
Floor space required		1130L x 1241W mm	1150L x 1150W mm
Over height		1050 mm	1000 mm
Weight	Net weight	1600 kgs	1200 kgs
	Gross weight	1850 kgs	1450 kgs

**Please call if you need further assistance.
Thanks for visiting truformequipment.com**