



FU WEI

Bushing Cut-Off 2Die 3Blow with Fingerless Transfer

MODEL DESCRIPTION	UL-2305	UL-2310	UL-2315
(MM)WIRE DIAMETER	Φ1.2-Φ2.5	Φ1.4-Φ3.5	Φ1.6-Φ4.5
(MM)CUT-OFF LENGTH	2~14	3~25	3~30
(MM)KO LENGTH /MAX	14	25	30
BLANK PER MIN MAX	50-120 PCS	50-110 PCS	50-100 PCS
(MM)MAIN SLIDER STROKE	45	60	92
(MM)MAIN UP/DOWN STROKE	26	26	32
(MM)P.K.O. STROKE	non	3rd 10	3rd 12
MAIN MOTOR	1HP-6P	3HP-6P	5HP-4P
(MM)1ST DIE DIA.	Φ14x25L	Φ20x35L	Φ22x62L
(MM)2ND DIE DIA.	Φ20x35.3L	Φ30x50.3L	Φ34.5x80.5L
(MM)1ST PUNCH DIA.	Φ14x50L	Φ16x40L	Φ18x70L
(MM)2ND PUNCH DIA.	Φ18 x50L	Φ26x63L	Φ28x75L
(MM)THIRD PUNCH DIA.	Φ18 x50L	Φ18 x63L	Φ25x75L
(MM)CUT-OFF DIA.	φ12	φ15	φ19
(MM)CUTTER	6X20X55	8X24X70	9x32x75
N.W.KG	750	1000	1450
G.W.KG	850	1100	1550
(CM)OVERALL DIMENSION(LxWxH)	210X120X147	225X112X148	225x112x148

**Please call if you need further assistance.
Thanks for visiting truformequipment.com**