















THI-18R,20R,22R,25R, THREAD ROLLING MACHINE

	仕様				転造圧	出力	回転数	ダイスポケット	ストローク	ダイスサイズ	重量	タンク容量								
	Threads without points												Threads pressure	Power	Speeds	Standard die pockets	Standard stroke	Standard die	Weight (net)	Coolant (litros)
	Max	Max	Max	Max																
																				
18R	M18	150	50	80	26,500kg	4P 22kW	43 55 70 (3steps)	L W H 284×47×165 320×60×165	630	L W H 280×50×50 310×50×50	10ton	120 ℓ								
20R	M20	180	80	100	27,800kg	4P 30kW	37 47 60 (3steps)	L W H 305×62×200 340×65×200	680	L W H 300×60×60 330×60×60	13ton	150 ℓ								
22R	M22	180	50	100	30,800kg	4P 30kW	37 47 60 (3steps)	L W H 320×62×200 350×65×200	720	L W H 320×60×60 350×60×60	13ton	150 ℓ								
25R	M27	300	80	220	40,300kg	4P 45kW	31 37 44 (3steps)	L W H 403×73×250 470×73×250	940	L W H 400×60×85 450×60×85	23ton	140 ℓ								

Please call if you need further assistance.
Thanks for visiting truformequipment.com

**Please call if you need further assistance.
Thanks for visiting truformequipment.com**